

DRAFT

Title 8 – Building Regulations

Chapter 11 – Rental Housing Code

Sections

8-11-1 General

8-11-2 Rental Facility License Required

8-11-3 Rental Facility License Issuance

8-11-4 Rental Facility Inspection

8-11-5 Rental Facility License Revocation

8-11-6 Change in License Application Information or Transfer of Property

8-11-7 Rental Facility Standards

8-11-8 Definitions

8-11-1 General

A. Title

This chapter and all provisions incorporated in this chapter, by reference or otherwise, shall be known as the Rental Housing Code of the City of Muscatine Code and hereafter will be referred to as this "Chapter".

B. Intent

The purpose of this Chapter is to provide minimum standards to safeguard life or limb, health, property and public welfare by regulating and controlling the use, occupancy and maintenance of all residential rental buildings and related structures within the city and to establish a program of regular rental inspections.

C. Scope

The provisions of this chapter shall apply to all buildings or portions thereof which are non-owner occupied; for which are used or intended to be used for human occupancy; and which requires a payment in money, goods, labor, service to be made by the occupant to the owner for the possession or use thereof.

D. Violation

Any person who shall violate a provision of this Chapter, or fail to comply therewith, or with any of the requirements thereof, shall be subject to a fine and/or municipal infraction as provided for in Chapter 3 of Title 1 of City Code, the amount of which shall be established by resolution of the city council and set out in Appendix D of this Code of Ordinances. Continued violations of this code may also result in revocation of a Rental Facility License in addition to any fines levied.

DRAFT

E. Other Codes and Regulations

1. This chapter shall be applied in conjunction with other chapters and titles of City Code and nothing in this chapter shall be interpreted as prohibiting or limiting enforcement by the Community Development Department or any other City departments any portion City Code as adopted and amended.
2. In cases where the provisions of this chapter are found to be in conflict with provisions of City Code or any applicable provision State or Federal law or regulations, the provisions which establish the higher standards for the promotion and protection of the health and safety of the people shall prevail.
3. Repairs, additions or alterations to a structure, or changes of occupancy, shall be done in accordance with the procedures and provisions City Code, which includes, but is not limited to the Building Code, Fire Code, Fuel Gas Code, Mechanical Code, Residential Code, Plumbing Code, and the Electrical Code.

F. Appeals

In any instance where a party is left aggrieved by an adverse action of the Building Official under this Chapter, such person shall have an opportunity to appeal the decision to the City Council or an equivalent Housing Appeals Board formed by Council as allowed by State law. The Council or equivalent board established by Council as allowed by law shall render all decisions and findings in writing to the appellant with a copy to the Building Official. Appeals shall be processed in accordance with the provisions contained in Section 8-5-11(B) of this Code.

8-11-2 Rental Facility License Required

No person shall rent, or offer for rent, any dwelling unit or rooming unit for use in whole or in part for human habitation, unless a valid Rental Facility License exists for each dwelling unit or rooming unit.

8-11-3 Rental Facility License Issuance

A. Application Requirements

1. The application shall be on such form and detail as prescribed by the Community Development Department.
2. An application for a Rental Facility License required by this Chapter shall be made to the Community Development Department at least 30 days prior to initial occupancy as a dwelling unit as rental facility.
3. Unless notified otherwise by the owner, an application for the renewal of an expiring Rental Facility License shall be deemed to be automatically submitted 60 days prior to expiration with no action required by the owner or authorized agent , using information on file for the rental facility which as per Section 8-11-8(B) has to be current with the Community Development Department.

DRAFT

B. Rental Facility License Inspection Fees

1. Rental Facility License inspection fees, including fees for reinspection and a fee for the inspection of an occupied but unlicensed rental facility, shall be as set forth by resolution of the City Council and as set out in Appendix D to this Code of Ordinances.
2. A Rental Facility License inspection fee shall be due 30 days from the scheduled inspection date.
3. **Late Payment Penalty**
 - a. A late payment penalty of a \$25 shall be added to a Rental Facility License inspection fee not paid by its due date.
 - b. If a Rental Facility License inspection fee is not paid within 30 days of its due date a monthly interest of 1.5% on, the original amount due plus the late payment penalty of \$25, shall be charged.
 - c. The city shall send a notice of the late payment penalty to an owner subject to the payment penalty by first class mail.
 - d. The late payment penalty and the interest shall not accrue if such owner files an appeal with the City, under the provision of Section 8-5-11, or the district court.
 - e. Any unpaid fee, penalty, or interest shall constitute a lien on the real property and may be collected in the same manner as a property tax.
 - f. Before a lien is filed, the City shall send a notice of intent to file a lien to the owner subject to the late payment penalty by first class mail to such owner.

(Code of Iowa, Sec. 364.17[5])

C. Grounds for Issuance

The Community Development Department shall issue a valid Rental Facility License to an applicant once all of the following criterial has been met.

1. Submission of a complete application, accurately providing all requested information, on forms provided by the Community Development Department.
2. The dwelling unit or rooming unit for which the Rental Facility License is being applied for passes the Rental Facility Inspection per the provisions of Section 8-11-4.

D. Period of Validity for a Rental Facility License

A Rental Facility License shall expire three years from the date of the initial Rental Facility License inspection.

DRAFT

8-11-4 Rental Facility License Inspection

A. Appointments for Inspections

1. Appointments for inspections for previously unregistered or new dwelling units or rooming units shall be scheduled by the Community Development Department upon receipt of a complete application for a Rental Facility License.
2. Inspections for the renewal of an expiring Rental Facility License shall be scheduled by the Community Development Department no sooner than 60 days prior to the expiration of the license. If necessitated by the availability of inspectors, the Community Development Department, at its discretion, may schedule the inspection later than 60 days prior to the expiration of expiring license, if this occurs, the validity of expiring license shall be extended so that it expires 60 days after the scheduled date of initial inspection.
3. The owner may request the appointment to be rescheduled. However, the inspection shall be performed within thirty days of the originally scheduled inspection date.
4. If a dwelling unit or rooming unit is vacant and is undergoing construction or repair the owner may request the appointment for inspection for said unit to be postponed until the construction/repair work has been completed.

B. Notice of Inspection

The owner shall notify all tenants of the inspection at least 24 hours prior to scheduled inspection, in accordance with Section 562A.19(3) of Iowa Code.

C. Inspection of All Areas of a Rental Facility

All areas necessary to determine compliance with the standards set forth in Section 8-11-7 shall be inspected. Should access not be obtained to all areas, a reinspection must be scheduled and an additional fee may be charged for each subsequent reinspection in accordance with the established fee schedule in Appendix D to this Code of Ordinances.

D. Inspection Standards

See Section 8-11-7

E. Notice of Failed Inspection and Order to Correct Violations

If the inspection determines that the condition of the dwelling unit or rooming unit violate any provision of this chapter, the Community Development Department shall give notice of the violation(s) to the owner of the rental facility. Such notice shall:

1. Be in writing;
2. Include a description of the real estate sufficient for identification;
3. Describe all violation(s) and remedial action(s) required.

DRAFT

4. State that work to correct all violations and/or all required remedial actions must be completed within 60 days of said notice, except for:
 - a. **Imminent Danger:** Work to correct a condition which could cause serious or life-threatening injury or death or due to structurally unsound conditions, any portion of the structure is likely to fall, be carried by the wind, or otherwise detach or move, and in doing so cause physical injury or damage to a person on the property or to a person or property nearby at any time shall require immediate corrective action.
 - b. **Seasonal Dependent Items:** Work must be completed by May 1st if all following conditions are presents; otherwise work must be completed within 60 days of said notice.
 - i. Work is not necessary to correct an imminent danger.
 - ii. Work is not necessary to maintain a temperature within the rental facility of not less than 68 degrees Fahrenheit.
 - iii. Work cannot be reasonably completed during periods of cold weather.
 - iv. The date that the notice is issued falls between September 1st and March 1st.
5. Advise that reinspection is required to verify correction of code deficiencies; that there is no charge for the reinspection; and that repairs or corrections have been completed and no Code deficiencies are cited on the second inspection, then a Rental Facility License shall be issued.
6. Advise that if the identified corrections and/or remedial actions are not complete necessitating a third inspection to verify compliance with the notice of violation and order to correct violations, then a fee shall be charged for the third inspection, and there shall be a fee for each additional fee charged for each succeeding reinspection, if such reinspection's are necessitated until full compliance is verified.
7. Advise that if a violation still exists upon reinspection, the Rental Facility License may be revoked and advise the potential fees and fines that may result from the revocation of a Rental Facility License.
8. Be mailed to the owner(s) of the rental facility.

F. Extension to an Order to Correct Violations

1. An owner may request an extension of time to complete any action to correct a violation or complete a required remedial action that cannot be completed by the deadline set forth of such a notice under the provision of Section 8-11-4(E) because of circumstances not of the owner(s) or are beyond the owner's control.

DRAFT

2. Such a request for an extension shall be made in writing to the Community Development Department.
3. Approval of an extension to an order to correct violations may be granted if the Community Development Department finds that:
 - a. Strict compliance with the deadline sets by the order to correct violations is impractical;
 - b. That the granting of such an extension does not violate the intent and purpose of City Code;
 - c. That granting the requested extension does not endanger the life, health, or safety of the occupants or the integrity of the structure.
4. Approval shall be made in writing and state:
 - a. The new deadline to correct said violation(s).
 - b. What specific code violation(s) that the extension applies to.

G. Substandard Building

Any building or portion thereof, including any dwelling, dwelling unit, rooming unit, guest room, or the premises on which the same is located, in which there exists a violation of City Code to the extent that the violation endangers the life, limb, health, property, safety, or welfare of the public or the occupant(s) thereof shall be deemed and hereby is declared to be a substandard building, and notices and procedures shall comply with Section 8-5-9, 8-5-10, 8-5-11, 8-5-12, 8-5-13, and 8-5-14.

H. Other Rental Inspections

Rental facilities may be inspected on a more frequent basis to ensure compliance with this code based upon one or more of the criteria listed below, there shall be no charge to the Rental Facility License holder for an inspection conducted as a result of these criteria. Any inspection conducted for the following reasons shall not fulfill the requirement for an inspection prior to issuance of or renewal of a Rental Facility License as required per Section 8-11-3(C)(2). If an inspection is performed under auspices of this section, the Rental Facility License holder shall be informed of the reason for said inspection.

1. Information is received indicating that there is a violation of provisions of City Code, or any state or federal regulations;
2. An observation is made by a Government official of a possible violation of the standards or the provisions of City Code or any state or federal laws and/or regulations;
3. Information is received indicating that a rental facility or rental unit is unoccupied and unsecured or that a rental unit is damaged by fire, water, or other causes detrimental to the structure;

DRAFT

4. A determination must be made whether there is compliance with a notice or an order issued by the Building Official;
5. A public health safety or welfare emergency is observed or is reasonably believed to exist;
6. A tenant makes a request for an inspection. If a tenant requests a nonemergency inspection, then the City of Muscatine shall give a written notice to the owner. Fourteen days after the written notification to the owner, an inspection may be conducted. In making such a request the tenant shall attach a dated copy of the notice in which he or she requested the owner or operator to correct the alleged violation, unless the complaint pertains to an emergency situation.
7. A property is declared a Dangerous or Unsafe Building or Structure pursuant to Section 9-3-3(R) of City Code; or
8. A property is declared a Substandard Building pursuant to Section 8-5-9 of City Code.

8-11-5 Rental Facility License Revocation or Denial of Renewal

A. Grounds for Revocation or Denial of Rental Facility License.

The Building Official may revoke or deny renewal of any Rental Facility License issued under this Subchapter where any of the following applies. False statements on any application or information or report required by this Subchapter to be given by the applicant, registrant, or permit holder:

1. Conviction or judgment of the licensee for violation of any provision of this Chapter;
2. Refusal by the owner to permit inspection by authorized personnel of the rental facility;
3. Failure to pay any application, penalty, reinspection, or reinstatement fee required by this Chapter as set out in Appendix D of this Code of Ordinances;
4. Failure to comply with a notice of violation and order to correct violations issued under the provision of Section 8-11-4(E);
5. Failure to comply with the provisions of the Title VIII of the Fair Housing Act of 1968 (as amended);
6. Declaration of status as a Dangerous or Unsafe Building or Structure pursuant to 9-3-3(R) of City Code;
7. Declaration of Status as dangerous or substandard building as defined by Section 8-5-9 of City Code;
8. Frequent and recurrent noncompliance with the provisions of this Chapter;

DRAFT

9. The time period imposed by the Building Official for correction of a code violation has been exceeded for the same violation more than two consecutive times and has required more than two consecutive reinspections to obtain code compliance.
- B. The owner of the affected rental facility shall be notified in writing by certified mail of the license revocation. An appeal may be submitted, within five business days of the notice, to the City Council or an equivalent Housing Appeals Board formed by Council as allowed by State law. The Council or equivalent board established by Council as allowed by law shall render all decisions and findings in writing to the appellant with a copy to the Building Official. Appeals shall be processed in accordance with the provisions contained in Section 8-5-11(B) of this Code.
- B. Reissuance of a Revoked Rental Facility License**

To reissue a revoked Rental Facility License, the procedure for the issuance of Rental Facility License set forth in Section 8-11-3 shall be followed, except that the Rental Facility License fees shall be as set forth by resolution of the City Council and as set out in Appendix D to this Code of Ordinances shall be doubled.
- C. A rental facility with a revoked license may be posted for no occupancy if:
 1. The physical condition of the dwelling unit or rooming unit warrants, in accordance with all applicable standards contained with Title 8 of City Code, posting for no occupancy.
 2. Access for any inspection authorized by this Chapter is denied.
- D. If an owner allows for occupancy of a rental facility after the Rental Facility License has been revoked they shall be subject to a fine and/or municipal infraction, the amount of which shall be equal to the penalty for allowing the occupancy of an unregistered rental unit set forth in Section 8-11-1(D).

8-11-6 Change in License Application Information or Transfer of Property

A. Transfer of Property

A Rental Facility License shall be transferable from one person to another at any time prior to its expiration, termination, or revocation. The owner or agent shall notify the city of any change of interest or ownership in the property within thirty days of any conveyance or transfer of interest affecting the property and provide the name and address of all persons who have acquired an interest therein. In the event the city has not been notified of such conveyance or transfer within the designated period of time, the rental license may be transferred from one owner or agent to another upon payment of a fee, the amount of which shall be established by resolution of the city council. The fees shall be assessed to the new owner or agent.

DRAFT

B. Change in License Application Information

Whenever there is a change in the information required for on the application for a Rental Facility License, the license holder or responsible agent shall notify the Community Development Department within thirty days of the change.

8-11-7 Rental Facility Standards

A. General Applicability

No person shall occupy or let to another for occupancy any dwelling unit, rooming unit, or part thereof which does not comply with the requirements of this section.

B. Interior Structure

1. Every foundation, roof, floor, wall, ceiling, stair, step, elevator, handrail, porch, guardrail, sidewalk, and appurtenance thereto shall be maintained in a safe and sound condition and shall be capable of supporting the loads that normal use may cause to be placed thereon.
2. The condition and equipment of interior and exterior stairs, halls, porches, and walkways must not present the danger of tripping and falling.
3. Peeling, blistered, or flaking paint shall be removed or effectively covered in a workmanlike manner so as to provide an easily cleaned finish.
4. Ceilings, walls, and floors must not have any serious defects such as severe bulging or leaning, large holes, loose surface materials, severe buckling, missing parts, or other serious damage.
5. Every supplied interior door shall fit reasonably well within its frame and shall be capable of being opened and closed properly; and securely attached to jambs, headers, or tracks as intended by the manufacturer of the attachment hardware.
6. Every supplied plumbing fixture and water and waste pipe shall be maintained in a good and sanitary working condition.
7. Water pressure shall be adequate to permit a proper flow of water from all open outlets at all times. (Except during maintenance and repair.)
8. **Maintenance of Gas Appliances and Facilities**
 - a. Every gas pipe shall be sound and tightly put together and shall be free of leaks, corrosion, and obstruction causing reduced pressure or volume.
 - b. Gas pressure shall be adequate to permit a proper flow of gas from all open gas valves at all times.

C. Exterior Structure

The exterior of a structure shall be maintained in good repair, structurally sound and sanitary so as not to pose a threat to the public health, safety or welfare.

DRAFT

1. Premises Identification

- a. Every building, except for accessory buildings, shall display an address number.
- b. These numbers shall be not less than four inches in height, contrasting sharply in color with the background on which they are affixed, and shall be placed in a position to plainly legible and visible from the street.
- c. Unit numbers for individual units within a building or complex shall be displayed on, above, or to the side of the doorway of each unit.
- d. The City shall assign the address number for each individual building.
- e. For buildings that contain more than one dwelling unit. The property owner shall assign a unit number for each individual dwelling unit.

2. Protective Treatment

- a. Exterior wood surfaces, other than decay-resistant woods, shall be protected from the elements and decay by painting or other protective covering or treatment.
- b. Peeling, flaking, and chipped paint shall be eliminated and surfaces repainted.
- c. All siding and masonry joints as well as those between the building envelope and the perimeter of windows, doors, and skylights shall be maintained weather resistant and water tight.
- d. All metal surfaces subject to rust or corrosion shall be coated to inhibit such rust and corrosion and all surfaces with rust or corrosion shall be stabilized and coated to inhibit future rust and corrosion. Surfaces designed for stabilization by oxidation are exempt from this requirement.

3. Structural members

All structural members shall be maintained free from deterioration and shall be capable of safely supporting the imposed dead and live loads.

4. Exterior Walls

All exterior walls shall be maintained free from holes, breaks, and loose or rotting materials.

5. Foundation Walls

All foundation walls shall be maintained safe and free from open cracks, holes, breaks, or other serious defects so to prevent entry of vermin and air infiltration.

DRAFT

6. Roofs, Gutters, and Downspouts

- a. The roof and flashing shall be sound, tight and not have defects that admit rain.
- b. All roof drainage shall be adequate to prevent dampness or deterioration in the walls or interior portion of the structure.
- c. Roof drains, gutters and downspouts shall be maintained in good repair and free from obstructions.
- d. Rainwater shall be directed away from the building so as to prevent water damage to the building.

7. Decorative Features

All cornices, belt courses, corbels, terra cotta trim, wall facings, and similar decorative features shall be maintained in good repair with proper anchorage and in a safe condition.

8. Overhang Extensions

All overhang extensions including, but not limited to canopies, marquees, signs, metal awnings, fire escapes, standpipes, and exhaust ducts shall be maintained in good repair and be properly anchored so as to be kept in a sound condition.

9. Stairways, Decks, Porches, & Balconies

- a. Every stair, ramp, landing, balcony, porch, deck, or other walking surface shall be maintained in sound condition and good repair.
- b. Every exterior stairway, deck, porch, balcony, and all appurtenances attached thereto shall be maintained structurally sound, in good repair, with proper anchorage, and capable of supporting the imposed loads.

10. Chimneys and Towers

All chimneys, cooling towers, smoke stacks and similar appurtenances shall be maintained structurally safe and sound, and in good repair.

11. Windows

- a. Every window, including all associated hardware, shall be kept in sound condition, good repair, and weather tight.
- b. All glazing compound materials shall be maintained free from holes.
- c. Any openable window located in whole or in part within six feet above ground level or a walking surface below that provide access to a dwelling unit or rooming unit shall be equipped with a window sash locking device.

DRAFT

12. Doors – Exterior

- a. All exterior doors, door assemblies, and hardware shall be maintained in good condition.
- b. Locks at all entrance doors to dwelling units or rooming units shall secure such doors.
- c. Doors providing access to a dwelling unit or rooming unit shall be equipped with a lock designed to be readily openable from the side from which egress is to be made without the need for keys, special knowledge or effort. Such locks shall be installed according to the manufacturer's specifications and maintained in good working order.

13. Basement Hatchways

- a. Every basement hatchway shall be maintained to prevent the entrance of rodents, rain, and surface drainage water.
- b. Basement hatchways that provide access to a dwelling unit or rooming unit shall be equipped with devices that secure the units from unauthorized entry.

D. Ingress, Egress, & Access

1. Access to each dwelling unit or rooming unit shall not require first entering any other dwelling unit or rooming unit. **Exception:** Access to rooming units may be through a living room or kitchen of a unit occupied by the owner or operator of the structure.
2. No dwelling unit or rooming unit containing two or more sleeping rooms shall:
 - a. Have such arrangements that access to a bathroom or toilet room intended for use by occupants of more than one bedroom can be had only by going through another bedroom;
 - b. Bedrooms shall not constitute the only means of access to other bedrooms or habitable spaces and shall not serve as the only means of egress from other habitable spaces.
3. Every dwelling unit and rooming unit shall have access to two independent, unobstructed means of egress remote from each other. At least one shall be an exit which discharges directly to corridors or stairways or both to a public way. If both means of egress are to a common corridor, they shall be in opposite directions or in compliance with adopted building and/or fire codes.
4. Every means of egress shall comply with the following requirements:
 - a. Handrails. All stairways comprised of four or more risers shall be provided with a substantial and safely constructed handrail.

DRAFT

- b.** All unenclosed floor and roof openings, open and glazed sides of landings and ramps, balconies, or porches which are more than 30 inches above grade and any roof used for other than maintenance purposes shall be protected by a substantial and safely constructed guardrail.
 - c.** Every stairway shall have a reasonably uniform riser height and uniform tread width which shall be adequate for safe use.
 - d.** In basement dwelling units or rooming units where one means of egress is a window, such window shall have an unobstructed opening no less in area than that required in the adopted Building Code.
 - e.** No existing fire escape shall be deemed a sufficient means of egress unless it is in compliance with the fire codes of the State of Iowa and any applicable City rule or regulation.
 - f.** Every doorway providing ingress or egress from any dwelling unit, rooming unit, or habitable room shall be at least six feet, four inches (6' 4") high and twenty-four inches (24") wide.
- 5.** Every means of egress shall be maintained in good condition and shall be free of obstruction at all times. If the means of egress is a fire escape, it shall be maintained in a good state of repair.
- 6.** All means of egress doors shall be readily openable from the side from which egress is to be made without the need for keys, special knowledge, or effort, except where the door hardware conforms to that permitted by adopted Building Code.
- 7.** Every central heating unit, space heater, water heater, and cooking appliance shall be located and installed in such a manner so as to afford reasonable protection against interference of egress facilities or egress routes in the event of uncontrolled fire in the structure.
- 8.** Required emergency escape openings shall be maintained in accordance with the code in effect at the time of construction, and the following and the following provisions.
 - a.** Required emergency escape and rescue openings shall be operational from the inside of the room without the use of keys or tools.
 - b.** Bars, grilles, grates, or similar devices are permitted to be placed over emergency escape and rescue openings provided the minimum net clear opening size complies with the code that was in effect at the time of construction, and such devices shall be releasable or removable from the inside without the use of a key, tool or force greater than that which is required for normal operation of the escape and rescue opening.

DRAFT

E. Lighting

Lighting shall be provided as follows:

1. Every habitable room shall be provided with adequate natural and/or artificial light to permit normal indoor activities and to support the health and safety of the occupants.
2. Public passageways and stairways in structures accommodating three or more dwelling units or rooming units shall be provided with a convenient wall mounted light switch(es) which activates an adequate lighting system.
3. Exterior stairways serving individual dwelling units or rooming units shall be supplied with sufficient illumination to allow their safe use.

F. Fire Protection Equipment and Carbon Monoxide Alarms

All dwelling units or rooming units shall be provided with fire protection equipment and carbon monoxide alarms in accordance with the following provisions. These provisions at the time of adoption were compliant with the relevant portions of the Iowa Administrative Code and the Code of Iowa, if either change, the provisions which establish the higher standards for the promotion and protection of the health and safety of the people shall prevail.

1. Fire Extinguishers

- a. In all structures containing three or more dwelling units or rooming units shall be provide type 2A rated fire extinguishers, five pound minimum. One shall be provided on each floor, so located that they will be accessible to the occupants, and spaced so that no person will have to travel more than 75 feet from any point to reach the nearest extinguisher.
- b. All fire extinguishers shall be maintained in good working condition at all times.
- c. Occupant's shall not tamper with or disable any fire extinguisher. All tenants listed on the dwelling units or rooming units lease agreement shall be held responsible for any tampering or disabling within the unit and shall be subject to citation.

2. Smoke Detectors

All dwelling units and rooming houses shall be provided with carbon monoxide alarms in accordance with the following provisions:

a. Location and Installation

In accordance with 661 Iowa Administrative Code 210.3(11), smoke detectors shall be located as follows:

DRAFT

- iii. New and replacement smoke detectors installed after July 1, 2016, which receive their primary power from the building wiring where more than one smoke detectors is required to be installed shall be interconnected in such a manner that the activation of one alarm will activate all of the alarms.

3. Owner's Responsibility

- a. The owner shall be responsible for the installation and maintenance, excluding the replacement of batteries, of all smoke detectors.
- b. At every change of tenancy, where the occupancy of the departed tenant was of one month or more, it shall be the duty of the owner to test and ascertain that those smoke detectors contained in the unit are in operable condition, and if not, the owner shall be responsible for placing them in operable condition.
- c. The owner shall be responsible for the installation and maintenance, including the replacement of batteries, of all detectors and batteries located in common corridors and other areas required by law that are not under the direct control of the occupant(s).

4. Occupant's Responsibility

- a. The occupant shall be responsible for the replacement of all batteries necessary for the proper operation of all supplied smoke detectors within the portions of the rental facility directly under their control.
- b. The occupant shall be required to notify the owner, in writing, of any deficiencies, aside from the need for a need for new batteries, known to exist in a supplied detector(s), whereafter the owner has 24 hours in which to repair or replace in operable condition said smoke detector(s).
- c. Failure to keep batteries replaced, as necessary for safe operation of a supplied smoke detector, shall cause the occupant to be in violation of this Section and subject to a municipal infraction citation.
- d. The occupant shall not tamper with or disable any smoke detector. All tenants listed on the dwelling unit's lease agreement shall be held responsible for any tampering or disabling within the unit and shall be subject to citation.

DRAFT

5. Carbon Monoxide Alarms

All dwelling units and rooming houses shall be provided with carbon monoxide alarms in accordance with the following provisions:

a. Required Locations

A carbon monoxide alarm shall be installed in the following locations:

- i. In the immediate vicinity of every room used for sleeping purposes in each dwelling unit or rooming unit.
- ii. In each bedroom where a fuel-burning heater or furnace, fuel-burning appliance, or fireplace is located within the bedroom or its attached bathroom.
- iii. In each sleeping unit, if the sleeping unit or its attached bathroom contains a fuel-burning appliance, fuel-burning heater or furnace, or fireplace.
- iv. In the immediate vicinity of each sleeping unit where the sleeping unit or its attached bathroom does not contain a fuel-burning appliance, fuel-burning heater, or fireplace and is not served by a forced-air furnace.

b. Required Locations - Exceptions

A carbon monoxide alarm shall not be required in the locations specified by (Subsection a) when:

- i. There are no communicating openings between the fuel-burning heater or furnace, fuel-burning appliance, fireplace, or attached garage and a dwelling unit or sleeping unit.
- ii. There are no communicating openings between the fuel-burning heater or furnace, fuel-burning appliance or fireplace and a dwelling unit or sleeping unit and when a dwelling unit or sleeping unit is located more than one story above or below an attached garage.
- iii. There are no communicating openings between the fuel-burning heater or furnace, fuel-burning appliance, or fireplace and a sleeping unit or dwelling unit and the attached garage connects to the building through an open-ended corridor.
- iv. A carbon monoxide alarm is located on the ceiling of the room containing the fuel-burning heater, fuel-burning appliance or fireplace, or in the first room or area between the fuel-burning heater, fuel-burning appliance or fireplace and the dwelling unit or sleeping unit.

c. Forced-Air Furnace— Exception

A carbon monoxide alarm shall not be required in a dwelling unit or sleeping unit which is served by a fuel-burning forced-air furnace when a carbon monoxide alarm is located on the ceiling of the room containing the forced-air furnace or in the first room or area served by each main duct leaving the forced-air furnace and the carbon monoxide alarm signals are automatically transmitted to the occupants of each dwelling unit or sleeping unit served by the forced-air furnace.

d. Alternative Systems

i. Carbon Monoxide Detection Systems

Commercially installed carbon monoxide detection systems which have the capability of notifying all occupants of dwelling units or sleeping units within a building shall be an acceptable alternative to the installation of carbon monoxide alarms and shall be deemed compliant with this chapter.

ii. Combination Alarms

1. The carbon monoxide alarm may be combined with smoke detecting devices provided that the combined unit complies with the respective provisions of this chapter regarding smoke detectors and this chapter regarding carbon monoxide alarms or other reference standards and applicable codes.
2. A combined carbon monoxide alarm/smoke alarm shall emit different alarm signals for carbon monoxide and for smoke.
3. Combination carbon monoxide alarm/smoke alarms shall be an acceptable alternative to carbon monoxide alarms.

e. Power Source

i. New Construction

1. In buildings for which construction is begun on or after July 1, 2018, carbon monoxide alarms shall receive their primary power from the building wiring when such wiring is served from a commercial source.
2. Wiring shall be permanent and without a disconnecting switch other than that required for overcurrent protection.
3. Carbon monoxide alarms shall be equipped with a battery backup.

ii. Existing Building

New and replacement carbon monoxide alarms installed in buildings, already in existence, constructed or officially authorized prior to July 1, 2018, may be solely battery operated or may plug into an electrical socket and have a battery backup.

f. Responsibility for Installation and Maintenance of Carbon Monoxide Alarms

i. Owner's Responsibility

1. It is the responsibility of the owner to install carbon monoxide alarms.
2. It is the responsibility of the owner to ensure that the batteries are in operating condition at the time at the time the occupant takes possession of the dwelling unit.
3. If a carbon monoxide alarm is found to be inoperable, the owner shall promptly provide for repair or replacement of the carbon monoxide alarm.
4. The owner is responsible for providing written information regarding carbon monoxide alarm testing and maintenance to one occupant of the dwelling unit.
5. The owner shall, upon request of a tenant who has a hearing impairment, install light-emitting carbon monoxide alarms.

ii. Occupant's Responsibility

1. An owner may require an occupant who has a residency longer than 30 days to be responsible for general maintenance, including but not limited to replacement of any required batteries of the carbon monoxide alarms in the occupant's dwelling unit, and for testing the carbon monoxide alarms within the occupants dwelling unit.
2. The occupant is responsible for notifying the owner or manager in writing of any deficiencies that the lessee, tenant, guest or roomer cannot correct.
3. The occupant shall not tamper with or disable any carbon monoxide alarms. All tenants listed on the dwelling unit's or rooming unit's lease agreement shall be held responsible for any tampering or disabling within the unit and shall be subject to citation.

DRAFT

G. Bathrooms

1. Every dwelling unit shall contain the following:
 - a. A toilet
 - b. A bathtub or shower
 - c. A lavatory basin within or adjacent to the room containing the toilet
2. Every toilet and bath shall be contained within a room which will afford privacy to the user and shall be separated from a food preparation area by a tight-fitting door.
3. Every toilet, lavatory basin, and bathtub or shower shall be properly connected to an approved water and sewer system as required by City Code.
4. All toilets, bathtubs, showers, and lavatory basins shall be maintained in good working condition.
5. Every toilet room and/or bathroom floor surface shall be maintained so as to permit them to be kept in a clean, dry, and sanitary condition.
6. **Rooming Houses**
 - a. Not less than one toilet, lavatory basin, and bathtub or shower shall be supplied for each four rooming units.
 - b. Communal toilets and baths shall be located on the same floor or the floor immediately above or below the rooming unit.

H. Kitchens

1. Every dwelling unit shall have a kitchen or kitchenette equipped with the following:
 - a. A kitchen sink, meeting all applicable code requirements, connected to an approved water and sewer system as provided for in City Code.
 - b. The dwelling unit must have adequate space and utility hook-ups for a refrigerator, and a stove or range. The equipment may be supplied by either the owner or the occupant. All equipment provided by the owner must be in proper operating condition.
 - c. Space for the sanitary storage of food, dishes and cooking utensils.
 - d. The kitchen floor surface shall be maintained so as to permit it to be kept in a clean, dry, and sanitary condition
2. If a communal kitchen is supplied, it shall comply with the following requirements:
 - a. The minimum floor area of communal kitchens shall be 60 square feet.

DRAFT

- b.** Floor area in communal kitchens which permits roomers to prepare and eat meals shall either be 100 square feet or shall contain a communal dining room which complies with the following requirements:

 - 1.** Every communal dining room shall be located on the same floor as the communal kitchen and located as nearly adjacent to the communal kitchen as is practicable.
 - 2.** The communal dining room shall contain a table and adequate chairs for the normal use of the facilities.
 - 3.** Every communal dining room shall contain not less than 70 square feet of floor area.
- c.** The kitchen shall contain adequate food storage capacity, an approved sink, and a stove or range.
- d.** It shall include at least one cabinet of size suitable for the storage of food and eating and cooking utensils.
- e.** It shall contain a table and adequate chairs for the normal use of the facilities if a communal dining room is not supplied.
- f.** Every communal kitchen and communal dining room shall be located within a room accessible to the occupants of each rooming unit sharing the use of such kitchen, without going outside of the dwelling and without going through a dwelling unit or rooming unit of another occupant.
- g.** The kitchen floor surface shall be maintained so as to permit it to be kept in a clean, dry, and sanitary condition.

3. Cooking in Rooming Units

No owner shall knowingly allow the use of cooking equipment, except for a microwave, within any rooming unit.

I. Water Heating Facilities

- 1.** Every kitchen sink, bathtub or shower, and lavatory basin required in accordance with the provisions of this Chapter shall be properly connected with supplied water heating facilities.
- 2.** Where two separate handles control the hot and cold water, the left-hand control of the faucet where facing the fixture fitting outlet shall control the hot water. Faucets and diverters shall be connected to the water distribution system so that hot water corresponds to the left side of the fixture fitting. Single-handle mixing valves installed in showers and tub-shower combinations shall have the flow of hot water corresponding to the markings on the fixture fitting.

DRAFT

3. Every supplied water heating facility shall be properly connected and shall be capable of heating water to such a temperature as to permit an adequate amount of water to be drawn on every kitchen sink and lavatory basin required at a temperature of not less than 110 degrees Fahrenheit (43 degrees Centigrade).
4. Every water heater shall be protected against overheating by appropriate pressure and temperature limit controls.
5. Every water heater shall be properly installed and maintained in a safe working condition, and shall be capable of performing the intended functions.
6. Every fuel-burning water heater shall be shall be installed and maintained in a safe condition as required in the adopted mechanical code, this code and any other applicable code, law or regulation.
7. Every fuel-burning water heater shall be equipped with an electronic ignition or with a pilot light and an automatic control to interrupt the flow of fuel to the unit in the event of failure of the ignition device.
8. Not be located within any sleeping room or bathroom unless there is adequate combustion air, an automatic shutoff is provided, and the continuing operation of the water heater poses no threat to the occupant, as determined by the Building Official.

J. Heating Facilities

1. Every dwelling and rooming unit shall have heating facilities which are properly installed and are capable of safely and adequately heating all habitable rooms, bathrooms and toilet rooms located therein to a temperature of at least 68 degrees Fahrenheit (20 degrees Celsius) at a distance of three feet above the floor level at all times. The heating facilities shall be so designed and equipped that heat, as specified in this subsection, is available for all dwelling units and rooming units.
2. The heating equipment of each dwelling shall be maintained in a good, safe working condition and shall be capable of heating all habitable rooms and bathrooms located therein to the minimum temperature required by this Chapter.
3. Every fuel-burning heating unit shall be effectively vented in a safe manner to a chimney or duct leading to the exterior of the building. The chimney duct and vent shall be of such design as to assure proper draft and shall be adequately supported.
4. Every steam or hot water boiler shall be protected against overheating by appropriate pressure and temperature limit controls.

DRAFT

5. Every fuel-burning space heating unit and water heater shall be equipped with an electronic ignition or with a pilot light and an automatic control to interrupt the flow of fuel to the unit in the event of failure of the ignition device.
6. No fuel-burning furnace shall be located within any sleeping room or bathroom unless there is adequate combustion air, an automatic shutoff is provided, and the continuing operation of the furnace poses no threat to the occupant, as determined by the Building Official.

K. Maintenance of Heating and Supplied Cooling Facilities

1. The heating equipment and supplies cooling facilities of each dwelling shall be maintained in a good, safe working condition and shall be capable of heating all habitable rooms and bathrooms located therein to the minimum temperature required by this Chapter.

L. Ventilation

1. Required Natural Ventilation of Habitable Rooms

All habitable room shall have adequate natural meeting the following standards.

- a. At least one window or door in good repair located on an outside wall that is capable of being opened to admit fresh air.
- b. Screens, meeting the following criteria, shall be provided on any window or door that is necessary to provide the required natural ventilation of habitable room.
 1. Any window or door being used to provide the required ventilation for a room must have a screen of not less than 16 mesh per inch.
 2. Screens shall be maintained in good repair and be free from tears, holes, or other imperfections of either screen or frame that would admit insects such as flies or mosquitoes.
 3. If a screen door is being used to provide the required ventilation it shall have a self-closing device in good working condition.

2. Required Ventilation of Bathrooms and Toilet Rooms

All bathrooms and toilet rooms must be provided with natural ventilation that meets the standards set forth in Subsection 1 or be provided with a mechanical ventilation system that is capable of producing 2 air changes per hour.

3. Mechanical Ventilation

If provided any mechanical ventilation system shall meet the following criteria.

- a. All mechanical ventilation systems providing required ventilation shall be kept in good working order.

DRAFT

- b.** No mechanical exhaust system, exhausting vapors, gases, or odors shall be discharged into an attic, crawl space, or cellar unless such attic, crawl space, or cellar is adequately vented to the outside.

M. Electrical Requirements

- 1.** The electrical system shall not by reason of overloading, dilapidation, lack of insulation, improper fusing, or for any other cause, expose the occupants to hazards of electrical shock or fire, and every electrical outlet, switch, and fixture shall be maintained in good and safe working condition.
- 2.** Every habitable room shall contain at least two separate floor or wall-type electric double convenience outlets which shall be properly installed, on adjacent walls or otherwise separated for reasonable access from all spaces within the room.
- 3.** Every toilet room, bathroom, laundry room, furnace room, basement, and cellar shall contain at least one supplied ceiling or wall-type electric light fixture, and one floor or wall-type electrical outlet which shall be properly installed.
- 4.** Ground-fault circuit-interrupter protection for personnel shall be provided in the following locations:
 - a.** Bathrooms
 - b.** Garages and accessory buildings with a floor located at or below grade level not intended as habitable rooms and limited to storage areas, work areas, and areas of similar use
 - c.** Outdoors
 - d.** Crawl Spaces - at or below grade level
 - e.** Unfinished portions of areas of the basement not intended as habitable rooms
 - f.** Kitchens - where the receptacles are installed to serve the counter top surfaces
 - g.** Sinks - where receptacles are installed within 6 feet from the top of the inside edge of the bowl of the sink
 - h.** Bathtubs or shower stalls - where receptacles are installed within 6 feet of the outside edge of the bathtub or shower stall
 - i.** Laundry Areas

DRAFT

5. Extension Cord/Temporary Wiring

- a. Extension No temporary wiring may be used in any dwelling or dwelling unit except as approved by the Electrical Inspector or other authorized inspector under the adopted Electrical Code.
- b. Extension cords may be used to connect portable electric loads to a source of power. Such cords may not be used where the electric current to be supplied would exceed the cord's carrying capacity.
- c. Extension cords may not be passed through open doorways or windows or under floor coverings; they may not be placed in such a position that the passage of traffic over them could result in damage to the insulation.
- d. Multiplug adapters, such as cube adapters, unfused plug strips or any other device not complying with the electrical code as adopted by the City shall be prohibited.
- e. Power strips (relocatable power tap) may only be used when they are equipped with an overcurrent device, are of the polarized or grounded type, and shall be listed in accordance with UL 1363. These power strips must plug directly into the wall no other power strips, extension cords, or multiplug adapters may be plugged into the power strip.

N. Pest Extermination

1. Every occupant of a single-family dwelling unit shall be responsible for the extermination of any insects, rodents, or other pests on the premises.
2. Every occupant of a structure containing two or more dwelling units or rooming units shall be responsible for such extermination within the unit occupied by him or her whenever said unit is the only one infested. However, whenever it is determined by the Health Officer, or his or her designate, that infestation is caused by failure of the owner to maintain the structure in a reasonably rodent proof and/or insect proof condition, extermination shall be the responsibility of the owner.
3. The property owner shall be responsible for extermination of pests when it is determined by the Building Official, that the infestation is present in two or more dwelling units or rooming units within a structure.

O. Accessory Buildings

1. Every foundation, exterior wall, roof, window, exterior door, and appurtenance of every accessory structure shall be so maintained as to prevent the structure from becoming a harborage for rats or other vermin and shall be maintained in a reasonably watertight, structurally sound condition capable of withstanding imposed wind and snow loads.

DRAFT

2. Every accessory building and/or garage shall be secured against unauthorized entry. It shall be the responsibility of the person(s) having the possession and use of the accessory building to comply with this Section.

P. Lead Based Paint

Every owner or operator of a dwelling unit or rooming house shall comply with HUD Lead Based Paint Regulations, 24 CFR, Part 35, issued pursuant to the Lead Based Paint Poisoning Prevention Act.

Q. Minimum Space and Occupancy Standards

1. Dwelling Units Containing Only One Habitable Room (I.E. Efficiency Unit, Studio Apartments, Etc.)

Shall contain at least 120 square feet of floor space for the first occupant; at least 220 square feet of floor space for two occupants; and at least 320 square feet for three occupants.

2. Dwelling Units Containing Two Or More Habitable Rooms and Rooming Units

Every bedroom shall contain not less than 70 square feet and every bedroom occupied by more than one person shall contain not less than 50 square feet of floor area for each occupant thereof.

3. Minimum space and occupancy standards shall be the minimum requirements established in the Housing Quality Standards as adopted, and amended by the United States Department of Housing and Urban Development.

4. A dwelling unit shall not exceed occupancy maximums.

5. No occupant shall allow the occupancy of any dwelling unit or rooming unit within which he or she resides to exceed the occupancy standards outlined in Section 8-5-5 of this Code.

R. Ceiling Height

The ceiling height in every habitable room shall be at least six feet, eight inches (6' 8"). In addition, obstructions of space by such items as water and gas pipes, cabinetry, etc. shall be permitted when such obstructions are located in such a fashion that they do not interfere with normal or emergency ingress and egress and are approved by the Community Development Department.

S. Occupant Responsibility for Controlled Areas

1. Every occupant of a dwelling unit or rooming unit shall keep in a clean, safe, and sanitary condition that part of the dwelling, dwelling unit, rooming unit, or premises thereof he or she occupies and controls, to include:
 - a. Every floor and floor covering shall be kept reasonably clean and sanitary.
 - b. Every wall and ceiling shall be kept reasonably clean and free of dirt or greasy film.

DRAFT

- c. No dwelling unit or rooming house shall be used for the storage or handling of refuse, except as provided in City Code.
 - d. Plumbing Fixtures. The occupants of a dwelling unit shall keep all supplied plumbing fixtures therein in a clean and sanitary condition and shall be responsible for the reasonable care, proper use, and proper operation thereof.
 - e. Occupants shall not knowingly overload the circuitry of the dwelling unit or rooming unit.
 - f. The use of extension cords and power strips shall comply with Section 8-11-7(M)(5).
2. Any occupant who shall violate a provision of this section, or fail to comply therewith, or with any of the requirements thereof, shall be subject to a fine and/or municipal infraction as provided for in Chapter 3 of Title 1 of City Code.

T. Mobile Homes

All mobile homes shall be provided with two frame ties and two over-the-top tiedowns equal to or better than the specifications outlined in booklet TR-75 published by the Department of Defense.

DRAFT

8-11-9 Definitions

A. Scope

Unless otherwise expressly stated, the following terms shall, for the purposes of this Chapter, have the meanings shown in this section.

B. Interchangeability

Words stated in the present tense include the future; words stated in the masculine gender include the feminine and neuter; the singular number includes the plural and the plural, the singular.

C. Terms not defined

Where terms are not defined through the methods authorized by this section, such terms shall have ordinarily accepted meanings such as the context implies.

Abate - To end a nuisance, emergency, or nonconformance.

Bathroom - A room containing plumbing fixtures including a bathtub or shower.

Bedroom - Any room or space used or intended to be used for sleeping purposes in either a dwelling unit or sleeping unit.

Building – Any structure used or intended for supporting or sheltering any use or occupancy.

Building Official - the Community Development Director or official designee, or any duly authorized representative of the City of Muscatine who is charged with the administration and enforcement of this Chapter.

Carbon Monoxide Alarm - One or more devices, including but not limited to combination carbon monoxide alarm/smoke alarms, which detect carbon monoxide gas for the purpose of alerting occupants by a distinct audible signal, which incorporate a sensor, control components, and an alarm notification appliance in a single unit operated from a power source either in the unit or obtained at the point of installation, and which meet the standards established by the Underwriters Laboratories (UL). All carbon monoxide alarms shall meet the requirements of the National Fire Protection Association (NFPA) Standard 720, 2013 edition, and be UL listed in accordance with UL 2034.

Carbon Monoxide Detection System - A system or portion of a combination system which consists of a control unit, components, and circuits arranged to monitor and annunciate the status of carbon monoxide alarm initiating devices and to initiate the appropriate response to those signals, and which meets the standards established by the Underwriters Laboratories (UL). All carbon monoxide detection systems shall meet the requirements of the National Fire Protection Association (NFPA) Standard 720, 2013 edition, shall display a label or other identification issued by an approved testing agency, and shall be UL listed in accordance with UL 2075.

City Code – The Municipal Code of the City of Muscatine, Iowa, 2015.

Communicating Opening - A door, window, or any other opening which allows air to be exchanged between a fuel-burning appliance or garage and a sleeping unit or dwelling unit.

DRAFT

Dwelling unit - A room or suite of rooms used for human habitation which provide complete, independent living facilities for one or more persons, including permanent provisions for living, sleeping, eating, cooking and sanitation.

Egress - An arrangement of exit routes to provide a means of exit from buildings and/or premises

Escape and Rescue Opening – An operable window, door, or similar device that provides for a means of escape and access for rescue in the event of an emergency.

Extermination - The control and elimination of insects, rats or other pests by eliminating their harborage places; by removing or making inaccessible materials that serve as their food; by poison spraying, fumigating, trapping or by any other approved pest elimination methods.

Fuel - Coal, kerosene, oil, fuel gases, or other petroleum products or hydrocarbon products such as wood that emit carbon monoxide as a byproduct of combustion.

Fuel-Burning or Fuel-Fired

An appliance, heater, furnace, or fireplace which uses and combusts fuel as part of its designed use.

Good Repair - properly installed, safe, stable, and maintained sufficiently free of defects or deterioration so as to be functional for current use.

Guard - A building component or a system of building components located at or near the open sides of elevated walking surfaces (such as decks, porches, balconies, stairways) that minimizes the possibility of a fall from the walking surface to a lower level.

Habitable Room – room or enclosed space having a minimum of 70 square feet of total floor area within a dwelling unit or rooming unit used or intended to be used for living, sleeping, cooking and eating purposes, excluding bathrooms, toilet rooms, pantries, laundries, foyers, corridors, closets, storage spaces and stairways.

Habitable Space - Space in a structure for living, sleeping, eating or cooking. Bathrooms, toilet rooms, closets, halls, storage or utility spaces, and similar areas are not considered habitable spaces.

Imminent Danger - A condition which could cause serious or life-threatening injury or death or due to structurally unsound conditions, any portion of the structure is likely to fall, be carried by the wind, or otherwise detach or move, and in doing so cause physical injury or damage to a person on the property or to a person or property nearby at any time

Infestation - The presence, within or contiguous to, a structure or premises of insects, rats, vermin or other pests.

DRAFT

Listed - Equipment, materials, products or services included in a list published by an organization acceptable to the state fire marshal or local fire code official and concerned with evaluation of products or services that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services and whose listing states either that the equipment, material, product or service meets identified standards or has been tested and found suitable for a specified purpose. All carbon monoxide alarms, combination carbon monoxide alarm/smoke alarms, and carbon monoxide detection systems installed under these rules must be listed with the Underwriters Laboratories.

Open-ended corridor - An interior corridor that is open on each end and connects to an exterior stairway or ramp at each end with no intervening doors or separation from the corridor.

Operator - Any person who has charge, care or control of a structure or premises which is let or offered for occupancy.

Owner - Any person, agent, operator, firm or corporation having a legal or equitable interest in the property; or recorded in the official records of the state, county or municipality as holding title to the property; or otherwise having control of the property, including the guardian of the estate of any such person, and the executor or administrator of the estate of such person if ordered to take possession of real property by a court.

Rental Facility – Any dwelling unit or rooming house; or part thereof for the owner has or intends has entered into a written or verbal agreement with a person to exchange some cash, goods, or services in exchange for permission to occupy the dwelling, as a residence, for a specified period of time.

Rental Facility License - a license issued by the City of Muscatine which grants the owner or operator the option of letting a dwelling unit for rent and showing that the dwelling unit for which it is issued was in compliance with the applicable provisions of this chapter at the time of issuance.

Rooming Unit - Any room or group of rooms forming a single habitable unit occupied or intended to be occupied for sleeping or living, but not for cooking purposes.

Rooming House - A building arranged or occupied for lodging, with or without meals, for compensation and not occupied as a one- or two-family dwelling.

Rooming Unit - Any room or group of rooms forming a single habitable unit occupied or intended to be occupied for sleeping or living, but not for cooking purposes.

Sanitary – a clean condition which guards against disease, illness or infection, or the growth of harmful bacteria.

Separate Sleeping Area -An area containing bedrooms which is separated from the sleeping area by a use area such as a kitchen or living room (but not a bathroom).

Sleeping Area - An area of a dwelling unit containing bedrooms which are separated from each other by no use area other than a bathroom.

DRAFT

Sleeping Unit - A room or space in a building in which people sleep, which can also include permanent provisions for living, eating, and either sanitation or kitchen facilities, but not both. Such rooms and spaces that are also part of a dwelling unit are not sleeping units. Rooming units in which people sleep are also sleeping units.

Structure – That which is built or constructed.

Toilet Room - A room containing a toilet or urinal but not a bathtub or shower.

Tenant - In the context of this Chapter, an occupant of a rental dwelling unit who has entered into a written or verbal agreement to exchange some cash, goods, or services in exchange for permission to occupy the dwelling, as a residence, for a specified period of time.

U.L. Listed - Tested and listed by Underwriters' Laboratories, Inc.

Vermin - cockroaches, mice, rats, and similar pests that carry disease.

Workmanlike - Executed in a skilled manner; e.g., generally plumb, level, square, in line, undamaged and without marring adjacent work.